#### CESSNA 150 – N2918S CHECKLIST

Verbally verify each item & completion of sections.

#### **PRE-FLIGHT INSPECTION**

PAVE / IMSAFE / W & B – COMPLETE Cabin / Electrical

1. Documents – A.R.R.O.W.

2. Control Lock & Pitot Cover - REMOVE

3. Ignition Switch – OFF

4. Avionics Master - OFF

5. Battery – ON

6. Flaps – FULL DOWN

7. Fuel Gauges / Electric Gyro – CHECK

8. Lights & Pitot Heat – CHECK

9. Battery - OFF

#### Empennage

1. Empennage Surface – CHECK 2. Horizontal Stabilizer - SECURE 3. Elevator & Trim Tab – FREE & SECURE 4. Rudder – FREE & SECURE 5. Tail Tie-down – DISCONNECT 6. Antennas – CHECK CONDITION **Right Wing** 1. Fuel Tank Sump – SAMPLE & CHECK 2. Tire – CHECK TREAD & PRESSURE 3. Brake - CHECK FOR LEAKS 4. Flap – CHECK 5. Aileron – FREE & SECURE 6. Wingtip / Leading Edge – CHECK 7. Wing Tie-Down – DISCONNECT 8. Fuel Quantity - VERIFY / CAP SECURE Nose 1. Engine Oil – CHECK LEVEL (4-6 quarts) 2. Fuel Strainer – SAMPLE & CHECK 3. Propeller / Spinner – CHECK 4. Air Filter – CHECK CLEAR 5. Nose Strut – CHECK 6. Tire – CHECK TREAD/PRESSURE 7. Static Port – CHECK CLEAR 8. Windshield – CLEAN Left Wing 1. Fuel Quantity - VERIFY / CAP SECURE 2. Pitot Tube – CHECK CLEAR 3. Stall Warning Opening – CHECK CLEAR 4. Fuel Tank Vent - CHECK CLEAR 5. Wing Tie-Down – DISCONNECT 6. Leading Edge / Wingtip – CHECK 7. Aileron – FREE & SECURE 8. Flap – CHECK

- 9. Tire CHECK TREAD & PRESSURE
- 10. Brake CHECK FOR LEAKS
- 11. Fuel Tank Sump SAMPLE & CHECK
- 12. Ladder & Chocks REMOVE & STOW

## **BEFORE STARTING ENGINE**

1. Pre-flight – **COMPLETE** 2. Passenger Briefing – S.A.F.E.T.Y. 3. Seats & Seatbelts - ADJUST & SECURE Fuel Shutoff Valve – ON 5. Avionics Master – OFF 6. Electrical Equipment - OFF 7. All Circuit Breakers - IN STARTING ENGINE 1. Brakes – TEST & HOLD 2. Mixture – RICH 3. Throttle - OPEN ½ INCH 4. Carb Heat – OFF 5. Beacon Light – ON 6. Master Switch - ON 7. Prime – AS REQUIRED (3 MAX) 8. Propeller Area – "CLEAR!" 9. Ignition - KEYS BOTH / PUSH TO START 10. Throttle - 1000 RPM 11. Oil Pressure - CHECK IN GREEN 12. Wing Flaps – UP 13. Mixture – LEAN 1 INCH FOR TAXI PRE-TAXI & TAXI 1. Avionics Master – ON 2. Transponder – STANDBY 3. ATIS – CHECK 4. Clearance – OBTAIN 5. Transponder – SET CODE & SET TO "ALT" 6. Brakes - CHECK (BOTH PILOT STATIONS) 7. Instruments - CHECK DURING TAXI (IFR) **BEFORE TAKEOFF (RUN-UP)** 1. (C)ontrols - FREE & CORRECT 2. (I) nstruments - SET 3. (G)as - Fuel Shutoff Valve ON 4. (A)ttitude (Trim/Flaps) – SET (10° Soft Field)

5. (R)adios – COM / NAV / TRANSPONDER

6. (S)ecure - DOORS / WINDOWS LATCHED

7. Brakes – HOLD

8. Throttle - 1700 RPM

- Mixture LEAN 1 INCH
- Mags LEFT/RIGHT (125 MAX DROP)
- Ammeter CHECK (NEUTRAL OR +)
- Oil Pressure / Temp CHECK IN LIMITS
- Suction IN GREEN
- Carb Heat ON, VERIFY RPM DROP
- Throttle IDLE CHECK
- Carb Heat OFF
- 9. Throttle 1000 RPM
- 10. Throttle Friction Lock ADJUST
- 11. Clearance REVIEW
- 12. Takeoff Emergency Briefing **COMPLETE**

V Speeds (MPH) Vr = 50 Vx = 52 Vy = 72Va = 109 Vg = 65 Vref = 60-70

#### CESSNA 150 – N2918S CHECKLIST

Verbally verify each item & completion of sections.

## PRE-FLIGHT INSPECTION

PAVE / IMSAFE / W & B – COMPLETE Cabin / Electrical 1. Documents – A.R.R.O.W. 2. Control Lock & Pitot Cover - REMOVE 3. Ignition Switch – OFF 4. Avionics Master - OFF 5. Battery – ON 6. Flaps – FULL DOWN 7. Fuel Gauges / Electric Gyro – CHECK 8. Lights & Pitot Heat – CHECK 9. Battery – OFF Empennage 1. Empennage Surface – CHECK 2. Horizontal Stabilizer – SECURE 3. Elevator & Trim Tab – FREE & SECURE 4. Rudder – FREE & SECURE 5. Tail Tie-down – DISCONNECT 6. Antennas - CHECK CONDITION **Right Wing** 1. Fuel Tank Sump – SAMPLE & CHECK 2. Tire - CHECK TREAD & PRESSURE 3. Brake - CHECK FOR LEAKS 4. Flap – CHECK 5. Aileron – FREE & SECURE 6. Wingtip / Leading Edge – CHECK 7. Wing Tie-Down – DISCONNECT 8. Fuel Quantity - VERIFY / CAP SECURE Nose 1. Engine Oil – CHECK LEVEL (4-6 quarts) 2. Fuel Strainer – SAMPLE & CHECK 3. Propeller / Spinner – CHECK 4. Air Filter – CHECK CLEAR 5. Nose Strut – CHECK 6. Tire – CHECK TREAD/PRESSURE 7. Static Port – CHECK CLEAR 8. Windshield – CLEAN Left Wing 1. Fuel Quantity - VERIFY / CAP SECURE 2. Pitot Tube – CHECK CLEAR 3. Stall Warning Opening - CHECK CLEAR 4. Fuel Tank Vent - CHECK CLEAR 5. Wing Tie-Down – DISCONNECT 6. Leading Edge / Wingtip – CHECK 7. Aileron – FREE & SECURE 8. Flap – CHECK 9. Tire – CHECK TREAD & PRESSURE 10. Brake – CHECK FOR LEAKS 11. Fuel Tank Sump – SAMPLE & CHECK 12. Ladder & Chocks – REMOVE & STOW **BEFORE STARTING ENGINE** 1. Pre-flight – COMPLETE 2. Passenger Briefing – S.A.F.E.T.Y. 3. Seats & Seatbelts - ADJUST & SECURE Fuel Shutoff Valve – ON 5. Avionics Master – OFF 6. Electrical Equipment - OFF 7. All Circuit Breakers – IN STARTING ENGINE 1. Brakes – TEST & HOLD 2. Mixture – RICH 3. Throttle – OPEN ½ INCH 4. Carb Heat – OFF 5. Beacon Light – ON 6. Master Switch - ON 7. Prime - AS REQUIRED (3 MAX) 8. Propeller Area – "CLEAR!" 9. Ignition - KEYS BOTH / PUSH TO START 10. Throttle – 1000 RPM 11. Oil Pressure – CHECK IN GREEN 12. Wing Flaps – UP 13. Mixture - LEAN 1 INCH FOR TAXI PRE-TAXI & TAXI 1. Avionics Master - ON 2. Transponder – STANDBY 3. ATIS – CHECK 4. Clearance – OBTAIN 5. Transponder – SET CODE & SET TO "ALT" 6. Brakes - CHECK (BOTH PILOT STATIONS) 7. Instruments – CHECK DURING TAXI (IFR) BEFORE TAKEOFF (RUN-UP) 1. (C)ontrols - FREE & CORRECT 2. (I)nstruments – SET 3. (G)as – Fuel Shutoff Valve ON 4. (A)ttitude (Trim/Flaps) – SET (10° Soft Field) 5. (R)adios – COM / NAV / TRANSPONDER 6. (S)ecure - DOORS / WINDOWS LATCHED 7. Brakes - HOLD 8. Throttle – **1700 RPM** - Mixture - LEAN 1 INCH - Mags - LEFT/RIGHT (125 MAX DROP) Ammeter – CHECK (NEUTRAL OR +) - Oil Pressure / Temp - CHECK IN LIMITS - Suction - IN GREEN - Carb Heat - ON, VERIFY RPM DROP Throttle – IDLE CHECK - Carb Heat – OFF 9. Throttle – **1000 RPM** 10. Throttle Friction Lock - ADJUST 11. Clearance – REVIEW 12. Takeoff Emergency Briefing – **COMPLETE** 

V Speeds (MPH) Vr = 50 Vx = 52 Vy = 72Va = 109 Vg = 65 Vref = 60-70

#### TAKEOFF

- 1. All Lights ON 2. Mixture - RICH BELOW 3000 FEET 3. Throttle – FULL FORWARD
- Elevator RAISE NOSE Vr 50 MPH
- 5. Pitch Vx 52 / Vy 72 MPH

#### ENROUTE CLIMB

1. Flaps - UP ABOVE 200 FEET

2. Pitch – 75 MPH

### CRUISE

- 1. Power SET PER POH (MAX 75%)
- 2. Elevator TRIM FOR LEVEL FLIGHT
- 3. Mixture LEAN PER POH
- 4. Gauges MONITOR

# **BEFORE LANDING**

- 1. (A)Itimeter SET
- 2. (L)ights ON
- 3. (G)as Fuel Shutoff Valve ON
- 4. (U)ndercarriage CHECKED
- (M)ixture RICH BELOW 3000 FEET
- 6. (P)ower Carb Heat & Throttle ADJUST
- 7. (S)eatbelts ADJUST

### LANDING

- 1. Flaps SET BELOW 100 MPH
- 2. Airspeed 60 70 MPH (60 Short Field)
- 3. Braking MINIMUM REQUIRED

## AFTER LANDING

- 1. Wing Flaps UP
- 2. Mixture LEAN 1 INCH FOR TAXI
- 3. Carb Heat OFF
- 4. Lights (Except Beacon) OFF
- 5. Trim RESET FOR TAKEOFF
- SHUTDOWN
- 1. Transponder 1200 THEN STANDBY
- 2. Avionics Master OFF
- 3. Ignition Grounding CHECK
- 4. Mixture IDLE CUTOFF
- 5. Ignition OFF/KEYS OUT
- 6. Master Switch OFF

Rev 02

- 7. Control Lock / Pitot Cover INSTALL
- 8. Tie Downs CONNECT
- 9. Record HOBBS, TACH, ADDITIONS OF FUEL & OIL, POST FLIGHT CHECK



THIS CHECKLIST IS FOR REFERENCE ONLY **ALWAYS CONSULT AIRCRAFT POH** 

### **ENGINE FAILURE AFTER TAKEOFF**

1.	Pitch – <b>65 MPH</b>
2.	Flaps – <b>DOWN</b>
3.	Fuel Shutoff Valve – <b>OFF</b>
4.	Mixture – IDLE CUTOFF
5.	Ignition & Master Switches – OFF
6.	Doors – OPEN BEFORE TOUCHDOWN
EN	IGINE FAILURE IN FLIGHT
1.	(A)irspeed – 65 MPH & TRIM
2.	(B)est Landing Site – FLY DIRECT
3.	(C)ockpit Flow / (C)hecklist "Floor to door"
	<ul> <li>Fuel Shutoff Valve – ON</li> </ul>
	<ul> <li>Mixture &amp; Throttle – ADJUST</li> </ul>
	- Carb Heat – ON
	<ul> <li>Ignition – LEFT / RIGHT / BOTH</li> </ul>
	<ul> <li>Primer – IN &amp; LOCKED</li> </ul>
IF	NO RESTART
4.	(D)eclare – MAYDAY (121.5, 7700 as req.)
E	(E)vocuto / (E)vit

5. (E)xecute / (E)xit Fuel Shutoff Valve – OFF - Mixture - IDLE CUTOFF - Ignition Switch – OFF - Flaps - AS REQUIRED - Master Switch – OFF Doors – OPEN BEFORE TOUCHDOWN ENGINE FIRE ON GROUND 1. CONTINUE CRANKING - If engine starts: 1700 RPM THEN SHUTDOWN 2. If no start: SHUTDOWN - Ignition – OFF Master Switch – OFF - Fuel Shutoff Valve - OFF - Fire - EXTINGUISH

## ELECTRICAL FIRE IN FLIGHT

- 1. Master Switch OFF 2. All Switches Except Ignition – OFF 3. Vents/Cabin Air/Heat - CLOSED/OFF 4. Fire - EXTINGUISH WHEN FIRE APPEARS OUT 5. Cabin – VENTILATE 6. Circuit Breakers - CHECK, DON'T RESET 7. Master Switch – ON 8. Radios & Elec Equip - ON ONE AT A TIME AMMETER EXCESSIVE CHARGE / DISCHARGE
- 1. Master Switch CYCLE OFF THEN ON
- 2. Alternator CB CHECK IN (IF DISCHARGE) 3. If Condition Remains:
  - Alternator OFF
  - Electrical Load REDUCE

  - Flight TERMINATE AS SOON AS PRACTICAL

# TAKEOFF

- 1. All Lights ON
- 2. Mixture RICH BELOW 3000 FEET
- 3. Throttle FULL FORWARD
- 4. Elevator RAISE NOSE Vr 50 MPH
- 5. Pitch Vx 52 / Vy 72 MPH

# ENROUTE CLIMB

- 1. Flaps UP ABOVE 200 FEET
- 2. Pitch 75 MPH

# CRUISE

- 1. Power SET PER POH (MAX 75%)
- 2. Elevator TRIM FOR LEVEL FLIGHT
- 3. Mixture LEAN PER POH
- 4. Gauges MONITOR

## **BEFORE LANDING**

- 1. (A)Itimeter SET
- 2. (L)ights ON
- 3. (G)as Fuel Shutoff Valve ON
- 4. (U)ndercarriage CHECKED
- 5. (M)ixture RICH BELOW 3000 FEET
- (P)ower Carb Heat & Throttle ADJUST
- 7. (S)eatbelts ADJUST

#### LANDING

- 1. Flaps SET BELOW 100 MPH
- 2. Airspeed 60 70 MPH (60 Short Field)
- 3. Braking MINIMUM REQUIRED

## AFTER LANDING

- 1. Wing Flaps UP
- 2. Mixture LEAN 1 INCH FOR TAXI
- 3. Carb Heat OFF
- 4. Lights (Except Beacon) OFF
- 5. Trim RESET FOR TAKEOFF

# SHUTDOWN

- 1. Transponder 1200 THEN STANDBY
- 2. Avionics Master OFF
- 3. Ignition Grounding CHECK
- 4. Mixture IDLE CUTOFF
- 5. Ignition OFF/KEYS OUT
- 6. Master Switch OFF

Rev 02

- 7. Control Lock / Pitot Cover INSTALL
- 8. Tie Downs CONNECT
- 9. Record HOBBS, TACH, ADDITIONS OF FUEL & OIL, POST FLIGHT CHECK



THIS CHECKLIST IS FOR REFERENCE ONLY ALWAYS CONSULT AIRCRAFT POH

1. Pitch – 65 MPH 2. Flaps - DOWN 3. Fuel Shutoff Valve - OFF 4. Mixture - IDLE CUTOFF 5. Ignition & Master Switches – OFF 6. Doors - OPEN BEFORE TOUCHDOWN ENGINE FAILURE IN FLIGHT 1. (A) irspeed – 65 MPH & TRIM 2. (B)est Landing Site – FLY DIRECT 3. (C)ockpit Flow / (C)hecklist "Floor to door" - Fuel Shutoff Valve - ON - Mixture & Throttle – ADJUST Carb Heat – ON - Ignition - LEFT / RIGHT / BOTH - Primer – IN & LOCKED IF NO RESTART 4. (D)eclare - MAYDAY (121.5, 7700 as req.) 5. (E)xecute / (E)xit - Fuel Shutoff Valve - OFF - Mixture - IDLE CUTOFF - Ignition Switch – OFF - Flaps - AS REQUIRED - Master Switch – OFF Doors – OPEN BEFORE TOUCHDOWN ENGINE FIRE ON GROUND 1. CONTINUE CRANKING - If engine starts: 1700 RPM THEN SHUTDOWN 2. If no start: SHUTDOWN - Ignition - OFF Master Switch – OFF - Fuel Shutoff Valve – OFF Fire – EXTINGUISH **ELECTRICAL FIRE IN FLIGHT** 1. Master Switch – OFF 2. All Switches Except Ignition – OFF 3. Vents/Cabin Air/Heat - CLOSED/OFF 4. Fire – EXTINGUISH WHEN FIRE APPEARS OUT 5. Cabin – VENTILATE

ENGINE FAILURE AFTER TAKEOFF

6. Circuit Breakers – CHECK, DON'T RESET

8. Radios & Elec Equip - ON ONE AT A TIME

2. Alternator CB - CHECK IN (IF DISCHARGE)

- Flight - TERMINATE AS SOON AS

1. Master Switch – CYCLE OFF THEN ON

AMMETER EXCESSIVE CHARGE / DISCHARGE

7. Master Switch - ON

3. If Condition Remains:

- Alternator – OFF

PRACTICAL

- Electrical Load – REDUCE