CESSNA 150 - N3038S CHECKLIST

Verbally verify each item & completion of sections.

PRE-FLIGHT INSPECTION

PAVE / IMSAFE / W & B – COMPLETE

Cabin / Electrical

- 1. Documents A.R.R.O.W.
- 2. Control Lock & Pitot Cover REMOVE
- 3. Ignition Switch OFF
- 4. Avionics Master OFF
- 5. Battery ON
- 6. Flaps **FULL DOWN**
- 7. Fuel Gauges / Electric Gyro CHECK
- 8. Lights & Pitot Heat CHECK
- 9. Battery OFF

Empennage

- 1. Empennage Surface CHECK
- 2. Horizontal Stabilizer SECURE
- 3. Elevator & Trim Tab FREE & SECURE
- 4. Rudder FREE & SECURE
- 5. Tail Tie-down DISCONNECT
- 6. Antennas CHECK CONDITION

Right Wing

- 1. Fuel Tank Sump SAMPLE & CHECK
- 2. Tire CHECK TREAD & PRESSURE
- 3. Brake CHECK FOR LEAKS
- 4. Flap CHECK
- 5. Aileron FREE & SECURE
- 6. Wingtip / Leading Edge CHECK
- 7. Wing Tie-Down DISCONNECT
- 8. Fuel Quantity VERIFY / CAP SECURE

Nose

- 1. Engine Oil CHECK LEVEL (4-6 quarts)
- 2. Fuel Strainer **SAMPLE & CHECK**
- 3. Propeller / Spinner CHECK
- 4. Air Filter CHECK CLEAR
- 5. Nose Strut CHECK
- 6. Tire CHECK TREAD/PRESSURE
- 7. Static Port CHECK CLEAR
- 8. Windshield CLEAN

Left Wing

- 1. Fuel Quantity VERIFY / CAP SECURE
- 2. Pitot Tube CHECK CLEAR
- 3. Stall Warning Opening CHECK CLEAR
- 4. Fuel Tank Vent CHECK CLEAR
- 5. Wing Tie-Down **DISCONNECT**
- 6. Leading Edge / Wingtip CHECK
- 7. Aileron FREE & SECURE
- 8. Flap CHECK
- 9. Tire CHECK TREAD & PRESSURE
- 10. Brake CHECK FOR LEAKS
- 11. Fuel Tank Sump SAMPLE & CHECK
- 12. Ladder & Chocks REMOVE & STOW

BEFORE STARTING ENGINE

- 1. Pre-flight COMPLETE
- 2. Passenger Briefing S.A.F.E.T.Y.
- 3. Seats & Seatbelts ADJUST & SECURE
- 4. Fuel Shutoff Valve ON
- 5. Avionics Master OFF
- 6. Electrical Equipment OFF
- 7. All Circuit Breakers IN

STARTING ENGINE

- 1. Brakes TEST & HOLD
- 2. Mixture RICH
- 3. Throttle OPEN 1/2 INCH
- 4. Carb Heat OFF
- 5. Beacon & Strobe Lights ON
- 6. Master Switch ON
- 7. Prime AS REQUIRED (3 MAX)
- 8. Propeller Area "CLEAR!"
- 9. Ignition KEYS BOTH / PUSH TO START
- 10. Throttle 1000 RPM
- 11. Oil Pressure CHECK IN GREEN
- 12. Wing Flaps UP
- 13. Mixture LEAN 1 INCH FOR TAXI

PRE-TAXI & TAXI

- 1. Avionics Master ON
- 2. Transponder STANDBY
- 3. ATIS CHECK
- 4. Clearance **OBTAIN**
- 5. Transponder SET CODE & SET TO "ALT"
- 6. Brakes CHECK (BOTH PILOT STATIONS)
- 7. Instruments CHECK DURING TAXI (IFR)

BEFORE TAKEOFF (RUN-UP)

- 1. (C)ontrols FREE & CORRECT
- 2. (I)nstruments SET
- 3. (G)as Fuel Shutoff Valve ON
- 4. (A)ttitude (Trim/Flaps) SET (10° Soft Field)
- 5. (R)adios COM / NAV / TRANSPONDER
- 6. (S)ecure DOORS / WINDOWS LATCHED
- 7. Brakes HOLD
- 8. Throttle 1700 RPM
 - Mixture LEAN 1 INCH
 - Mags LEFT/RIGHT (125 MAX DROP)
 - Oil Pressure / Temp CHECK IN LIMITS
 - Ammeter CHECK (NEUTRAL OR +)
 - Carb Heat ON, VERIFY RPM DROP
 - Throttle IDLE CHECK
 - Carb Heat OFF
- 9. Throttle 1000 RPM
- 10. Throttle Friction Lock ADJUST
- 11. Clearance REVIEW
- 12. Takeoff Emergency Briefing COMPLETE

V Speeds (MPH) Vr = 50 Vx = 52 Vy = 72Va = 109 Vg = 65 Vref = 60-70

CESSNA 150 - N3038S CHECKLIST

Verbally verify each item & completion of sections.

PRE-FLIGHT INSPECTION

PAVE / IMSAFE / W & B – COMPLETE

Cabin / Electrical

- 1. Documents A.R.R.O.W.
- 2. Control Lock & Pitot Cover REMOVE
- 3. Ignition Switch OFF
- 4. Avionics Master OFF
- 5. Battery ON
- 6. Flaps FULL DOWN
- 7. Fuel Gauges / Electric Gyro CHECK
- 8. Lights & Pitot Heat CHECK
- 9. Battery OFF

Empennage

- 1. Empennage Surface CHECK
- 2. Horizontal Stabilizer SECURE
- 3. Elevator & Trim Tab FREE & SECURE
- 4. Rudder FREE & SECURE
- 5. Tail Tie-down DISCONNECT
- 6. Antennas CHECK CONDITION

Right Wing

- 1. Fuel Tank Sump SAMPLE & CHECK
- 2. Tire CHECK TREAD & PRESSURE
- 3. Brake CHECK FOR LEAKS
- 4. Flap CHECK
- 5. Aileron FREE & SECURE
- 6. Wingtip / Leading Edge CHECK
- 7. Wing Tie-Down DISCONNECT 8. Fuel Quantity - VERIFY / CAP SECURE

Nose

- 1. Engine Oil CHECK LEVEL (4-6 quarts)
- 2. Fuel Strainer SAMPLE & CHECK
- 3. Propeller / Spinner CHECK
- 4. Air Filter CHECK CLEAR
- 5. Nose Strut CHECK
- 6. Tire CHECK TREAD/PRESSURE
- 7. Static Port CHECK CLEAR
- 8. Windshield CLEAN

Left Wing

- 1. Fuel Quantity VERIFY / CAP SECURE
- 2. Pitot Tube CHECK CLEAR
- 3. Stall Warning Opening CHECK CLEAR
- 4. Fuel Tank Vent CHECK CLEAR
- 5. Wing Tie-Down **DISCONNECT**
- 6. Leading Edge / Wingtip CHECK
- 8. Flap CHECK
- 9. Tire CHECK TREAD & PRESSURE
- 10. Brake CHECK FOR LEAKS
- 12. Ladder & Chocks REMOVE & STOW

- 7. Aileron FREE & SECURE
- 11. Fuel Tank Sump SAMPLE & CHECK

- 2. Passenger Briefing S.A.F.E.T.Y.
- 3. Seats & Seatbelts ADJUST & SECURE
- 4. Fuel Shutoff Valve ON

BEFORE STARTING ENGINE

1. Pre-flight - COMPLETE

- 5. Avionics Master OFF
- 6. Electrical Equipment OFF
- 7. All Circuit Breakers IN

STARTING ENGINE

- 1. Brakes TEST & HOLD
- 2. Mixture RICH
- 3. Throttle OPEN 1/2 INCH
- 4. Carb Heat OFF
- 5. Beacon & Strobe Lights ON
- 6. Master Switch ON
- 7. Prime AS REQUIRED (3 MAX)
- 8. Propeller Area "CLEAR!"
- 9. Ignition KEYS BOTH / PUSH TO START
- 10. Throttle 1000 RPM
- 11. Oil Pressure CHECK IN GREEN
- 12. Wing Flaps UP
- 13. Mixture LEAN 1 INCH FOR TAXI

PRE-TAXI & TAXI

- 1. Avionics Master ON
- 2. Transponder STANDBY
- 3. ATIS CHECK
- 4. Clearance OBTAIN
- 5. Transponder SET CODE & SET TO "ALT"
- 6. Brakes CHECK (BOTH PILOT STATIONS)
- 7. Instruments CHECK DURING TAXI (IFR)

BEFORE TAKEOFF (RUN-UP)

- 1. (C)ontrols FREE & CORRECT
- 2. (I)nstruments SET
- 3. (G)as Fuel Shutoff Valve ON
- 4. (A)ttitude (Trim/Flaps) SET (10° Soft Field)
- 5. (R)adios COM / NAV / TRANSPONDER
- 6. (S)ecure DOORS / WINDOWS LATCHED
- 7. Brakes HOLD 8. Throttle - 1700 RPM
 - Mixture LEAN 1 INCH
 - Mags LEFT/RIGHT (125 MAX DROP)
 - Oil Pressure / Temp CHECK IN LIMITS
 - Ammeter CHECK (NEUTRAL OR +) - Carb Heat - ON, VERIFY RPM DROP
 - Throttle IDLE CHECK
- Carb Heat OFF 9. Throttle - 1000 RPM
- 10. Throttle Friction Lock ADJUST
- 11. Clearance REVIEW
- 12. Takeoff Emergency Briefing COMPLETE

V Speeds (MPH) Vr = 50 Vx = 52 Vy = 72Va = 109 Vg = 65 Vref = 60-70

TAKEOFF

- 1. All Lights ON
- 2. Mixture RICH BELOW 3000 FEET
- 3. Throttle FULL FORWARD
- 4. Elevator RAISE NOSE Vr 50 MPH
- 5. Pitch Vx 52 / Vy 72 MPH

ENROUTE CLIMB

- 1. Flaps UP ABOVE 200 FEET
- 2. Pitch 75 MPH

CRUISE

- 1. Power SET PER POH (MAX 75%)
- 2. Elevator TRIM FOR LEVEL FLIGHT
- 3. Mixture LEAN PER POH
- 4. Gauges MONITOR

BEFORE LANDING

- 1. (A)Itimeter SET
- 2. (L)ights ON
- 3. (G)as Fuel Shutoff Valve ON
- 4. (U)ndercarriage CHECKED
- 5. (M)ixture RICH BELOW 3000 FEET
- 6. (P)ower Carb Heat & Throttle ADJUST
- 7. (S)eatbelts ADJUST

LANDING

- 1. Flaps SET BELOW 100 MPH
- 2. Airspeed 60 70 MPH (60 Short Field)
- 3. Braking MINIMUM REQUIRED

AFTER LANDING

- 1. Wing Flaps UP
- 2. Mixture LEAN 1 INCH FOR TAXI
- 3. Carb Heat OFF
- 4. Lights (Except Beacon) OFF
- 5. Trim RESET FOR TAKEOFF

SHUTDOWN

Rev 02

- 1. Transponder 1200 THEN STANDBY
- 2. Avionics Master OFF
- 3. Ignition Grounding CHECK
- 4. Mixture IDLE CUTOFF
- 5. Ignition OFF/KEYS OUT
- 6. Master Switch OFF
- 7. Control Lock / Pitot Cover INSTALL
- 8. Tie Downs CONNECT
- 9. Record HOBBS, TACH, ADDITIONS OF FUEL & OIL, POST FLIGHT CHECK



THIS CHECKLIST IS FOR REFERENCE ONLY **ALWAYS CONSULT AIRCRAFT POH**

ENGINE FAILURE AFTER TAKEOFF

- 1. Pitch 65 MPH
- 2. Flaps DOWN
- 3. Fuel Shutoff Valve OFF
- 4. Mixture IDLE CUTOFF
- 5. Ignition & Master Switches OFF
- 6. Doors OPEN BEFORE TOUCHDOWN

ENGINE FAILURE IN FLIGHT

- 1. (A)irspeed 65 MPH & TRIM
- 2. (B)est Landing Site FLY DIRECT
- 3. (C)ockpit Flow / (C)hecklist "Floor to door"
 - Fuel Shutoff Valve ON
 - Mixture & Throttle ADJUST
 - Carb Heat ON
 - Ignition LEFT / RIGHT / BOTH
 - Primer IN & LOCKED

IF NO RESTART

- 4. (D)eclare MAYDAY (121.5, 7700 as reg.)
- 5. **(E)**xecute / **(E)**xit
 - Fuel Shutoff Valve OFF
 - Mixture IDLE CUTOFF
 - Ignition Switch OFF
 - Flaps AS REQUIRED
 - Master Switch OFF
 - Doors OPEN BEFORE TOUCHDOWN

ENGINE FIRE ON GROUND

1. CONTINUE CRANKING

- If engine starts: 1700 RPM THEN **SHUTDOWN**
- 2. If no start: SHUTDOWN
 - Ignition OFF
 - Master Switch OFF
 - Fuel Shutoff Valve OFF
 - Fire EXTINGUISH

ELECTRICAL FIRE IN FLIGHT

- 1. Master Switch OFF
- 2. All Switches Except Ignition OFF
- 3. Vents/Cabin Air/Heat CLOSED/OFF
- 4. Fire EXTINGUISH

WHEN FIRE APPEARS OUT

- 5. Cabin VENTILATE
- 6. Circuit Breakers CHECK, DON'T RESET
- 7. Master Switch ON

8. Radios & Elec Equip - ON ONE AT A TIME AMMETER EXCESSIVE CHARGE / DISCHARGE

- 1. Master Switch CYCLE OFF THEN ON
- 2. Alternator CB CHECK IN (IF DISCHARGE)
- 3. If Condition Remains:
 - Alternator OFF
- Electrical Load REDUCE
- Flight TERMINATE AS SOON AS **PRACTICAL**

TAKEOFF

- 1. All Lights ON
- 2. Mixture RICH BELOW 3000 FEET
- 3. Throttle FULL FORWARD
- 4. Elevator RAISE NOSE Vr 50 MPH
- 5. Pitch Vx 52 / Vy 72 MPH

ENROUTE CLIMB

- 1. Flaps UP ABOVE 200 FEET
- 2. Pitch 75 MPH

- 1. Power SET PER POH (MAX 75%)
- 2. Elevator TRIM FOR LEVEL FLIGHT
- 3. Mixture LEAN PER POH
- 4. Gauges MONITOR

BEFORE LANDING

- 1. (A) Itimeter SET
- 2. (L)ights ON
- 3. (G)as Fuel Shutoff Valve ON
- 4. (U)ndercarriage CHECKED
- 5. (M)ixture RICH BELOW 3000 FEET
- 6. (P)ower Carb Heat & Throttle ADJUST
- 7. (S)eatbelts ADJUST

LANDING

- 1. Flaps SET BELOW 100 MPH
- 2. Airspeed 60 70 MPH (60 Short Field)
- 3. Braking MINIMUM REQUIRED

AFTER LANDING

- 1. Wing Flaps UP
- 2. Mixture LEAN 1 INCH FOR TAXI
- 3. Carb Heat OFF
- 4. Lights (Except Beacon) OFF
- 5. Trim RESET FOR TAKEOFF

SHUTDOWN

- 1. Transponder 1200 THEN STANDBY
- 2. Avionics Master OFF
- 3. Ignition Grounding CHECK
- 4. Mixture IDLE CUTOFF
- 5. Ignition OFF/KEYS OUT
- 6. Master Switch OFF 7. Control Lock / Pitot Cover - INSTALL

& OIL, POST FLIGHT CHECK

- 8. Tie Downs CONNECT 9. Record - HOBBS, TACH, ADDITIONS OF FUEL



THIS CHECKLIST IS FOR REFERENCE ONLY **ALWAYS CONSULT AIRCRAFT POH**

ENGINE FAILURE AFTER TAKEOFF

- 1. Pitch 65 MPH
- 2. Flaps DOWN
- 3. Fuel Shutoff Valve OFF
- 4. Mixture IDLE CUTOFF
- 5. Ignition & Master Switches OFF

6. Doors - OPEN BEFORE TOUCHDOWN

ENGINE FAILURE IN FLIGHT

- 1. **(A)**irspeed **65 MPH & TRIM**
- 2. (B)est Landing Site FLY DIRECT
- 3. (C)ockpit Flow / (C)hecklist "Floor to door"
 - Fuel Shutoff Valve ON
 - Mixture & Throttle ADJUST
 - Carb Heat ON
 - Ignition LEFT / RIGHT / BOTH
 - Primer IN & LOCKED

IF NO RESTART

- 4. (D)eclare MAYDAY (121.5, 7700 as req.)
- 5. (E)xecute / (E)xit
 - Fuel Shutoff Valve OFF
 - Mixture IDLE CUTOFF
 - Ignition Switch OFF
 - Flaps AS REQUIRED - Master Switch - OFF
 - Doors OPEN BEFORE TOUCHDOWN

ENGINE FIRE ON GROUND

1. CONTINUE CRANKING

- If engine starts: 1700 RPM THEN
- **SHUTDOWN** 2. If no start: SHUTDOWN
 - Ignition OFF
 - Master Switch OFF
 - Fuel Shutoff Valve OFF

- Fire - EXTINGUISH

- **ELECTRICAL FIRE IN FLIGHT**
- 1. Master Switch OFF
- 2. All Switches Except Ignition OFF
- 3. Vents/Cabin Air/Heat CLOSED/OFF 4. Fire - EXTINGUISH
- WHEN FIRE APPEARS OUT
- 5. Cabin **VENTILATE**
- 6. Circuit Breakers CHECK, DON'T RESET
- 7. Master Switch ON 8. Radios & Elec Equip - ON ONE AT A TIME

AMMETER EXCESSIVE CHARGE / DISCHARGE

- 1. Master Switch CYCLE OFF THEN ON
- 2. Alternator CB CHECK IN (IF DISCHARGE)
- 3. If Condition Remains: - Alternator - OFF
 - Electrical Load REDUCE
 - Flight TERMINATE AS SOON AS PRACTICAL

Rev 02